




SILVER REFLECTIVE 50



Construction

Ply	2
Mil Thickness	2

Performance Specifications	Glass Type 1/4"	1/8"
Solar Energy Transmitted %	59	40
Solar Energy Absorbed %	32	41
Solar Energy Reflected %	9	19
Visible Light Transmitted %	63	51
Visible Light Reflected % - Interior	10	21
Visible Light Reflected % - Exterior	11	19
Ultraviolet Rejected %	99	99
Shading Coefficient	.79	.58
Solar Heat Reduction %	21	42
Total Solar Energy Rejected %	31	50
Glare Reduction %	30	43
Emissivity	.86	.72
U-Value	1.13	1.04



Film-To-Glass Installation Ratings Silver Reflective 50

Single Clear	1
Dual Clear	1
Single Tinted	1
Dual Tinted	1
Low-E	1

Film-To-Glass Installation Ratings

- 1** = Approved for TSF & IGU Seal Failure warranty coverage at no additional fee.
- 2** = NOT approved for TSF & IGU Seal Failure warranty coverage. Apply for coverage with fee.
- 3** = TSF & IGU Seal Failure warranty coverage is NOT available.

Important

Data created from testing of film installed on 1/8" and 1/4" thick clear float glass. Data is representative of actual production. Batch to batch variations are within industry standards.



SILVER REFLECTIVE 35



Construction

Ply	2
Mil Thickness	2

Performance Specifications	Glass Type 1/4"	1/8"
Solar Energy Transmitted %	59	31
Solar Energy Absorbed %	32	41
Solar Energy Reflected %	9	28
Visible Light Transmitted %	63	41
Visible Light Reflected % - Interior	10	28
Visible Light Reflected % - Exterior	11	29
Ultraviolet Rejected %	99	99
Shading Coefficient	.79	.49
Solar Heat Reduction %	21	51
Total Solar Energy Rejected %	31	58
Glare Reduction %	30	54
Emissivity	.86	.72
U-Value	1.13	1.05



Film-To-Glass Installation Ratings Silver Reflective 35

Single Clear	1
Dual Clear	1
Single Tinted	1
Dual Tinted	2
Low-E	2

Film-To-Glass Installation Ratings

- 1** = Approved for TSF & IGU Seal Failure warranty coverage at no additional fee.
- 2** = NOT approved for TSF & IGU Seal Failure warranty coverage. Apply for coverage with fee.
- 3** = TSF & IGU Seal Failure warranty coverage is NOT available.

Important

Data created from testing of film installed on 1/8" and 1/4" thick clear float glass. Data is representative of actual production. Batch to batch variations are within industry standards.



SILVER REFLECTIVE 20



Construction

Ply	2
Mil Thickness	2

Performance Specifications	Glass Type 1/4"	1/8"
Solar Energy Transmitted %	59	13
Solar Energy Absorbed %	32	38
Solar Energy Reflected %	9	49
Visible Light Transmitted %	63	18
Visible Light Reflected % - Interior	10	56
Visible Light Reflected % - Exterior	11	55
Ultraviolet Rejected %	99	99
Shading Coefficient	.79	.26
Solar Heat Reduction %	21	74
Total Solar Energy Rejected %	31	78
Glare Reduction %	30	80
Emissivity	.86	.64
U-Value	1.13	1.01



Film-To-Glass Installation Ratings Silver Reflective 20

Single Clear	1
Dual Clear	1
Single Tinted	1
Dual Tinted	2
Low-E	2

Film-To-Glass Installation Ratings

- 1** = Approved for TSF & IGU Seal Failure warranty coverage at no additional fee.
- 2** = NOT approved for TSF & IGU Seal Failure warranty coverage. Apply for coverage with fee.
- 3** = TSF & IGU Seal Failure warranty coverage is NOT available.

Important

Data created from testing of film installed on 1/8" and 1/4" thick clear float glass. Data is representative of actual production. Batch to batch variations are within industry standards.