



SPECIALTY WHITE OUT



Construction

Ply	1
Mil Thickness	2

Performance Specifications	Glass Type 1/4"	1/8"
Solar Energy Transmitted %	9	12
Solar Energy Absorbed %	49	41
Solar Energy Reflected %	42	47
Visible Light Transmitted %	8	8
Visible Light Reflected % - Interior	83	83
Visible Light Reflected % - Exterior	56	59
Ultraviolet Rejected %	99	99
Shading Coefficient	.26	.27
Solar Heat Reduction %	74	73
Total Solar Energy Rejected %	77	77
Glare Reduction %	91	91
Emissivity	.87	.87
U-Value	1.10	1.12



Film-To-Glass Installation Ratings Specialty White Out

Single Clear	1
Dual Clear	1
Single Tinted	1
Dual Tinted	3
Low-E	3

Film-To-Glass Installation Ratings

- 1** = Approved for TSF & IGU Seal Failure warranty coverage at no additional fee.
- 2** = NOT approved for TSF & IGU Seal Failure warranty coverage. Apply for coverage with fee.
- 3** = TSF & IGU Seal Failure warranty coverage is NOT available.

Important

Data created from testing of film installed on 1/8" and 1/4" thick clear float glass. Data is representative of actual production. Batch to batch variations are within industry standards.